



Specification:

Electrical Characteristics	Nominal Voltage	13.2V
	Nominal Capacity	40AH
	Energy	660Wh
	Internal Resistance	≤ 50mΩ
	Cycle life	>2000 cycles at 0.2C 100% DOD
	Months Self Discharge	<3%
	Efficiency of Charge	100% at 0.5C
	Efficiency of discharge	96~99% at 1C
Charge	Charge volt	14.6+/-0.2V
	Charge Mode	CC at 0.2C to 14.6V, then at CV14.6V to charge current less than 0.02C
	Charge Current	5A
	Max. Charge current	10A
	Charge cut off voltage	15.6V+/-0.2V
Discharge	Max. Continuous Current	40
	Max. Pulse Current	80A (<3s)
	Discharge Cut-off Voltage	10.8V
Environment	Charge Temperature	0°C to 45°C (32F to 113F) at 60±25% Relative Humidity
	Discharge Temperature	- 20°C to 60°C (-4F to 140F) at 60±25% Relative Humidity
	Storage Temperature	0°C to 40°C (32F to 104F) 60±25% Relative Humidity
	Water Dust Resistance	N/A
Mechanical	Cell Material	LiFePO4
	Case Material	ABS
	Dimensions (in./inch)	7.25"x6.75"x6"
	Weight (lbs.)	14.4 lbs.
	Terminal	M5 Knurled Knob
BMS	Protection function	Over charge protection, Over discharge protection, Over current protection, Short current protection, Balanced function, Temperature protection

Discharge Characteristic

